

# Premium Polymer Sealer

- 1. Introduction** ALEXSEAL Premium Polymer Sealer is a non-abrasive synthetic sealer designed for protecting surfaces painted with polyurethane. It is formulated with UV absorbers that will protect the paint from exposure to the sun and improve the coatings' life expectancy. ALEXSEAL Premium Polymer Sealer will leave behind a protective polymer coating which will seal the surface from the harsh elements of the marine environment. It is recommended to apply ALEXSEAL Premium Polymer Sealer every 3 to 4 months.
- 2. Range of application** ALEXSEAL Premium Polymer Sealer is used in combination with ALEXSEAL Topcoats to achieve a new radiant shine and eliminate weather-related graying.
- 3. Color** Viscous white liquid
- 4. Coverage** N.A.
- 5. Substrate pre-treatment** The surface must be washed with ALEXSEAL Premium Wash Down Concentrate, rinsed and wiped dry. Please follow the instructions for ALEXSEAL Premium Wash Down Concentrate.

WARNING: Do not use the sealer on un-cleaned surfaces as it will enclose the dirt and may lead to matting of the surface or system failures.

**6. Trade names** Base Material A5010 ALEXSEAL Premium Polymer Sealer 1 Pt & 1.25 Gal

**7. Mixing ratio** Mixing not necessary

- 8. Application**
1. Wash the surface with ALEXSEAL Premium Wash Down Concentrate, rinse and wipe dry. Follow the instructions for ALEXSEAL Premium Wash Down Concentrate.
  2. Shake ALEXSEAL Premium Polymer Sealer before applying the sealer on a clean dust free surface. Using a 100% cotton cloth. To achieve the best results and protection incorporate the sealer with a mechanical device into the paint surface.
  3. Allow ALEXSEAL Premium Polymer Sealer to dry to a haze. Do not allow the material to dry more than 6 hours before removing, as it may be more difficult to remove.
  4. Wipe off haze with a 100% clean, cotton cloth or microfiber towel.
  5. Multiple coats of ALEXSEAL Premium Polymer Sealer may be needed to protect water run-off areas.

**NOTE:**

ALEXSEAL recommends washing the surface once a week. Use ALEXSEAL Premium Wash Down Concentrate to minimize removal of the ALEXSEAL Premium Polymer Sealer.

- 9. Storage and Shelf Life** Do not freeze. If the original unopened ALEXSEAL Premium Polymer Sealer is stored in a cool and dry place the product has a shelf life of 24 months after production

It is possible to refill the smaller/suitable package (1 Pt) with the larger 1.25 Gal package by opening the cap and filling in the new material.

WARNING: Keep out of reach of children, avoid contact with eyes. If so, flush eyes liberally with water.  
FIRST AID: Get medical attention if swallowed.

**Professional Use Only**

**Page 1 of 1**

The information contained in this data sheet is based on our level of research and development. Revisal by the user with regard to the intended aim is necessary due to the diverse processing and application possibilities. Any liability on part of Mankiewicz for faulty applications and / or improper use is expressly excluded. The processing of the product must be fully documented by means of a paint application protocol.

Rev 01/23