

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 05.01.2024

Version number 19 (replaces version 18)

Revision: 05.01.2024

**SECTION 1: Identification of the substance/mixture and of the company/
undertaking**

- 1.1 Product identifier
- Trade name: Epifanes PU Speedcoat Comp. A
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- Sector of Use
 - SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
 - SU21 Consumer uses: Private households / general public / consumers
 - SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
 - SU19 Building and construction work
- Product category
 - PC9a Coatings and paints, thinners, paint removers
 - PC35 Washing and cleaning products (including solvent based products)
 - PC0 Other
- Process category
 - PROC11 Non industrial spraying
 - PROC7 Industrial spraying
 - PROC19 Manual activities involving hand contact
 - PROC10 Roller application or brushing
- Environmental release category
 - ERC5 Use at industrial site leading to inclusion into/onto article
 - ERC8c Widespread use leading to inclusion into/onto article (indoor)
 - ERC8f Widespread use leading to inclusion into/onto article (outdoor)
- Article category
 - AC11 Wood articles
 - AC7 Metal articles
- Application of the substance / the mixture
See our technical datasheet for application of this product.
- 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:
W.Heeren & Zoon bv.
Oosteinderweg 32
1432 AL Aalsmeer
Netherlands
tel.+31 297-360366
email: info@epifanes.nl
- Further information obtainable from: Research & Development.
- 1.4 Emergency telephone number: +61 7 5563 1222 (Monday-Friday 8:30am-5:00pm)

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



flame

Flam. Liq. 3

H226 Flammable liquid and vapour.

(Contd. on page 2)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 05.01.2024

Version number 19 (replaces version 18)

Revision: 05.01.2024

Trade name: Epifanes PU Speedcoat Comp. A

(Contd. of page 1)



Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008
- The product is classified and labelled according to the GB CLP regulation.
- Hazard pictograms



GHS02



GHS07

- Signal word Warning
- Hazard-determining components of labelling:
 - N-butyl acetate
 - Hydrocarbons, C9, aromatics. (Note-p).
 - Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate
 - Isobutyl methacrylate
 - 2-hydroxyethyl methacrylate
 - Methyl methacrylate
- Hazard statements
 - H226 Flammable liquid and vapour.
 - H317 May cause an allergic skin reaction.
 - H336 May cause drowsiness or dizziness.
 - H412 Harmful to aquatic life with long lasting effects.
- Precautionary statements
 - P102 Keep out of reach of children.
 - P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 - P260 Do not breathe dust/fume/gas/mist/vapours/spray.
 - P271 Use only outdoors or in a well-ventilated area.
 - P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
 - P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
 - P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
 - P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- 2.3 Other hazards
- Results of PBT and vPvB assessment
- PBT: Not applicable.

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 05.01.2024

Version number 19 (replaces version 18)

Revision: 05.01.2024

Trade name: Epifanes PU Speedcoat Comp. A

(Contd. of page 2)

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- 3.2 Mixtures
- Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29	N-butyl acetate Flam. Liq. 3, H226 STOT SE 3, H336 EUH066	25-50%
CAS: 128601-23-0 EC number: 918-668-5 Reg.nr.: 01-2119455851-35	Hydrocarbons, C9, aromatics. (Note-p). Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 STOT SE 3, H335-H336	2.5-10%
CAS: 110-43-0 EINECS: 203-767-1 Index number: 606-024-00-3 Reg.nr.: 01-2119902391-49	Heptan-2-one Flam. Liq. 3, H226 Acute Tox. 4, H302; Acute Tox. 4, H332	≤2.5%
CAS: 1065336-91-5 EC number: 915-687-0 Reg.nr.: 01-2119491304-40-0000	Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate Repr. 2, H361f Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Skin Sens. 1A, H317	≥0.25-<1%
CAS: 97-86-9 EINECS: 202-613-0 Index number: 607-113-00-X Reg.nr.: 01-2119488331-38	Isobutyl methacrylate Flam. Liq. 3, H226 Skin Irrit. 2, H315; Skin Sens. 1B, H317; STOT SE 3, H335	≥0.1-<0.3%

(Contd. on page 4)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 05.01.2024

Version number 19 (replaces version 18)

Revision: 05.01.2024

Trade name: Epifanes PU Speedcoat Comp. A

(Contd. of page 3)

CAS: 868-77-9 EINECS: 212-782-2 Index number: 607-124-00-X Reg.nr.: 01-2119490169-29	2-hydroxyethyl methacrylate ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	≥0.1-<0.3%
CAS: 80-62-6 EINECS: 201-297-1 Index number: 607-035-00-6 Reg.nr.: 01-2119452498-28	Methyl methacrylate ⚠ Flam. Liq. 2, H225 ⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	≥0.1-<0.3%

Additional information:

Note P: The substance does not have to be classified as a carcinogen or mutagen as can be shown that the substance contains less than 0.1% (w / w) benzene (EINECS No 200-753-7.). This note applies only to certain complex oil-derived substances in Part 3.

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- After inhalation:
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- After skin contact:
Immediately wash with water and soap and rinse thoroughly.
Immediately rinse with water.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed
No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed
No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents:
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- 5.2 Special hazards arising from the substance or mixture
During heating or in case of fire poisonous gases are produced.
No further relevant information available.

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 05.01.2024

Version number 19 (replaces version 18)

Revision: 05.01.2024

Trade name: Epifanes PU Speedcoat Comp. A

(Contd. of page 4)

- 5.3 Advice for firefighters
- Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions:
Prevent seepage into sewage system, workpits and cellars.
Inform respective authorities in case of seepage into water course or sewage system.
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- 6.4 Reference to other sections
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- Information about fire - and explosion protection:
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
Requirements to be met by storerooms and receptacles: No special requirements.
Information about storage in one common storage facility: Not required.
Further information about storage conditions: Keep container tightly sealed.
- 7.3 Specific end use(s) No further relevant information available.

GB

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 05.01.2024

Version number 19 (replaces version 18)

Revision: 05.01.2024

Trade name: Epifanes PU Speedcoat Comp. A

(Contd. of page 5)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

123-86-4 N-butyl acetate

WEL	Short-term value: 966 mg/m ³ , 200 ppm Long-term value: 724 mg/m ³ , 150 ppm
-----	---

110-43-0 Heptan-2-one

WEL	Short-term value: 475 mg/m ³ , 100 ppm Long-term value: 237 mg/m ³ , 50 ppm Sk
-----	--

80-62-6 Methyl methacrylate

WEL	Short-term value: 416 mg/m ³ , 100 ppm Long-term value: 208 mg/m ³ , 50 ppm
-----	--

123-86-4 N-butyl acetate

WEL	Short-term value: 966 mg/m ³ , 200 ppm Long-term value: 724 mg/m ³ , 150 ppm
-----	---

110-43-0 Heptan-2-one

WEL	Short-term value: 475 mg/m ³ , 100 ppm Long-term value: 237 mg/m ³ , 50 ppm Sk
-----	--

80-62-6 Methyl methacrylate

WEL	Short-term value: 416 mg/m ³ , 100 ppm Long-term value: 208 mg/m ³ , 50 ppm
-----	--

Regulatory information WEL: EH40/2020

DNEL (Derived No Effect Level) voor professionals

123-86-4 N-butyl acetate

Dermal	Acute / short-term - systemic effects.	11 mg/kg bw/day (Employees)
	Long-term - systemic effects.	11 mg/kg/day (Employees)
Inhalative	Long-term - local effects.	300 mg/m ³ (Employees)
	Short-term systemic effects.	600 mg/m ³ (Employees)
	Short term - local effects.	600 mg/m ³ (Employees)
	Long-term - systemic effects.	300 mg/m ³ (Employees)

128601-23-0 Hydrocarbons, C9, aromatics. (Note-p).

Dermal	Long-term systemic effects.	25 mg//kg/day (Employees)
Inhalative	Long-term - systemic effects.	150 mg/m ³ (Employees)

110-43-0 Heptan-2-one

Inhalative	Acute / short term - local defects	1,516 mg/m ³ (Employees)
------------	------------------------------------	-------------------------------------

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 05.01.2024

Version number 19 (replaces version 18)

Revision: 05.01.2024

Trade name: Epifanes PU Speedcoat Comp. A

(Contd. of page 6)

1065336-91-5 Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate

Dermal	Long-term - systemic effects.	1.8 mg/kg/day (Employees)
Inhalative	Long-term - systemic effects.	1.27 mg/m ³ (Employees)

97-86-9 Isobutyl methacrylate

Dermal	Long-term - systemic effects.	5 mg/kg/day (Employees)
Inhalative	Long-term - local effects.	409 mg/m ³ (Employees)
	Long-term - systemic effects.	415.9 mg/m ³ (Employees)

868-77-9 2-hydroxyethyl methacrylate

Dermal	Long-term - systemic effects.	1.3 mg/kg/day (Employees)
Inhalative	Long-term - systemic effects.	4.9 mg/m ³ (Employees)

80-62-6 Methyl methacrylate

Dermal	Long-term - systemic effects.	13.67 mg/kg/day (Employees)
Inhalative	Acute / short term - local defects	416 mg/m ³ (Employees)
	Long-term - local effects.	208 mg/m ³ (Employees)
	Long-term - systemic effects.	348.4 mg/m ³ (Employees)

· DNEL (Derived No Effect Level) for general audience

123-86-4 N-butyl acetate

Oral	Long-term systemic effects.	2 mg/kg bw/day (General population)
	Short-term - systemic effects.	6 mg/kg bw/day (General population)
Dermal	Long-term - systemic effects.	6 mg/kg bw/day (General population)
	Long-term - local effects.	35.7 mg/m ³ (General population)
	Short-term - systemic effects.	6 mg/kg (General population)
Inhalative	Long-term - systemic effects.	35.7 mg/m ³ (General population)
	Acute / short-term - systemic effects.	300 mg/m ³ (General population)
	Acute / short-term - local effects.	300 mg/m ³ (General population)

128601-23-0 Hydrocarbons, C9, aromatics. (Note-p).

Oral	Long-term systemic effects.	11 mg/kg bw/day (General population)
Dermal	Long-term - systemic effects.	11 mg/kg bw/day (General population)
Inhalative	Long-term - systemic effects.	32 mg/m ³ (General population)

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 05.01.2024

Version number 19 (replaces version 18)

Revision: 05.01.2024

Trade name: Epifanes PU Speedcoat Comp. A

(Contd. of page 7)

110-43-0 Heptan-2-one

Oral	Long-term systemic effects.	23.32 mg/kg bw/day (General population)
Dermal	Long-term - systemic effects.	23.32 mg/kg bw/day (General population)
Inhalative	Acute - systemic effects.	54.27 mg/kg bw/day (Employees)
	Long-term - systemic effects.	1,516 mg/m ³ (Employees)
		84.31 mg/m ³ (General population)
		394.25 mg/m ³ (Employees)

1065336-91-5 Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate

Oral	Long-term systemic effects.	0.18 mg/kg bw/day (General population)
Dermal	Long-term - systemic effects.	0.9 mg/kg bw/day (General population)
Inhalative	Long-term - systemic effects.	0.31 mg/m ³ (General population)

97-86-9 Isobutyl methacrylate

Dermal	Long-term - systemic effects.	3 mg/kg bw/day (General population)
	Long-term - local effects.	366.4 mg/m ³ (General population)
Inhalative	Long-term - systemic effects.	66.5 mg/m ³ (General population)

868-77-9 2-hydroxyethyl methacrylate

Oral	Long-term systemic effects.	0.83 mg/kg bw/day (General population)
Dermal	Long-term - systemic effects.	0.83 mg/kg bw/day (General population)
Inhalative	Long-term - systemic effects.	2.9 mg/m ³ (General population)

80-62-6 Methyl methacrylate

Oral	Long-term systemic effects.	8.2 mg/kg bw/day (General population)
Dermal	Long-term - systemic effects.	8.2 mg/kg bw/day (General population)
	Long-term - local effects.	1.5 mg/m ³ (General population)
Inhalative	Long-term - systemic effects.	74.3 mg/m ³ (General population)
	Long-term - local effects.	104 mg/m ³ (General population)

• PNECs

123-86-4 N-butyl acetate

Freshwater	0.18 mg/l (Freshwater)
Marine water	0.018 mg/l (Marine water)
Sediment (freshwater)	0.981 mg/kg sed dw (Freshwater)
Sediment (marine water)	0.098 mg/kg sed dw (Marine water)

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 05.01.2024

Version number 19 (replaces version 18)

Revision: 05.01.2024

Trade name: Epifanes PU Speedcoat Comp. A

(Contd. of page 8)

STP	35.6 mg/l (Segmentation, Targeting and Positioning)
Soil	0.09 mg/kg (soil)
110-43-0 Heptan-2-one	
Freshwater	0.098 mg/l (Freshwater)
Marine water	0.01 mg/l (Marine water)
Sediment (freshwater)	1.89 mg/kg sed dw (Freshwater)
Sediment (marine water)	0.189 mg/kg sed dw (Marine water)
STP	12.5 mg/l (Segmentation, Targeting and Positioning)
Soil	0.321 mg/kg (soil)
1065336-91-5 Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	
Freshwater	0.002 mg/l (Freshwater)
Marine water	0 mg/l (Marine water)
Sediment (freshwater)	1.05 mg/kg sed dw (Freshwater)
Sediment (marine water)	0.11 mg/kg sed dw (Marine water)
STP	1 mg/l (Segmentation, Targeting and Positioning)
Soil	0.21 mg/kg (soil)
97-86-9 Isobutyl methacrylate	
Freshwater	0.021 mg/l (Freshwater)
Marine water	0.002 mg/l (Marine water)
Sediment (freshwater)	5.89 mg/kg sed dw (Freshwater)
Sediment (marine water)	0.589 mg/kg sed dw (Marine water)
STP	10 mg/l (Segmentation, Targeting and Positioning)
Soil	1.16 mg/kg (soil)
868-77-9 2-hydroxyethyl methacrylate	
Freshwater	0.482 mg/l (Freshwater)
Marine water	0.482 mg/l (Marine water)
Sediment (freshwater)	3.79 mg/kg sed dw (Freshwater)
Sediment (marine water)	3.79 mg/kg sed dw (Marine water)
STP	10 mg/l (Segmentation, Targeting and Positioning)
Soil	0.476 mg/kg (soil)
80-62-6 Methyl methacrylate	
Freshwater	0.94 mg/l (Freshwater)
Marine water	0.094 mg/l (Marine water)
Sediment (freshwater)	10.2 mg/kg sed dw (Freshwater)
Sediment (marine water)	0.102 mg/kg sed dw (Marine water)
STP	10 mg/l (Segmentation, Targeting and Positioning)
Soil	1.48 mg/kg (soil)

Additional information: The lists valid during the making were used as basis.

(Contd. on page 10)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 05.01.2024

Version number 19 (replaces version 18)

Revision: 05.01.2024

Trade name: Epifanes PU Speedcoat Comp. A

(Contd. of page 9)

- 8.2 Exposure controls
- Appropriate engineering controls No further data; see section 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
- Respiratory protection:
Filter AX
In case of short or low load, breathing filter device; in the case of intensive or prolonged exposure, use a breathing apparatus independent of the surrounding air. A half-face mask for organic vapours and solvents according to EN140 type A1 or A2 is recommended.
- Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- Penetration time of glove material
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- For the permanent contact gloves made of the following materials are suitable:
PE gloves, recommended film thickness:> 0.7 mm.
For a touch of 30-120 minutes: gloves made of PVA, recommended material thickness: 0.7 mm.
- For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:
Butyl rubber, BR
- As protection from splashes gloves made of the following materials are suitable:
Gloves of nitrile rubber, recommended material thickness:> 0.3 mm, neoprene or butyl rubber, recommended material thickness:> 0.4 mm.

(Contd. on page 11)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 05.01.2024

Version number 19 (replaces version 18)

Revision: 05.01.2024

Trade name: Epifanes PU Speedcoat Comp. A

(Contd. of page 10)

- Eye/face protection



Tightly sealed goggles

SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and chemical properties
- General Information
- Physical state: Fluid
- Colour: According to product specification
- Odour: Characteristic
- Odour threshold: Not determined.
- Melting point/freezing point: Undetermined.
- Boiling point or initial boiling point and boiling range: 124-128 °C (123-86-4 N-butyl acetate)
- Flammability: Flammable.
- Lower and upper explosion limit
- Lower: 1.2 Vol % (123-86-4 N-butyl acetate)
- Upper: 7.5 Vol % (123-86-4 N-butyl acetate)
- Flash point: 24 °C
- Auto-ignition temperature: 370 °C (123-86-4 N-butyl acetate)
- Decomposition temperature: Not determined.
- pH: Not determined.
- Viscosity:
- Kinematic viscosity at 20 °C: 40 s (DIN 53211/4)
- Dynamic: Not determined.
- Solubility
- water: Fully miscible.
- Partition coefficient n-octanol/water (log value): Not determined.
- Vapour pressure at 20 °C: 10.7 hPa (123-86-4 N-butyl acetate)
- Vapour pressure at 50 °C: 55 hPa
- Density and/or relative density
- Density at 20 °C: 1.042 g/cm³
- Relative density: Not determined.
- Vapour density: Not determined.

- 9.2 Other information
- Appearance:
- Form: Fluid
- Important information on protection of health and environment, and on safety.
- Ignition temperature: Product is not selfigniting.

(Contd. on page 12)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 05.01.2024

Version number 19 (replaces version 18)

Revision: 05.01.2024

Trade name: Epifanes PU Speedcoat Comp. A

(Contd. of page 11)

· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Solvent content:	
· Organic solvents:	41.1 %
· VOC content:	41.13 %
	VOC content:
	428.6 g/l / 3.58 lb/gal
· Solids content:	58.9 %
· Change in condition	
· Evaporation rate	Not determined.
· Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Flammable liquid and vapour.
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:
No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products:
No dangerous decomposition products known.

GB

(Contd. on page 13)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 05.01.2024

Version number 19 (replaces version 18)

Revision: 05.01.2024

Trade name: Epifanes PU Speedcoat Comp. A

(Contd. of page 12)

SECTION 11: Toxicological information

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- Acute toxicity
Based on available data, the classification criteria are not met.

- LD/LC50 values relevant for classification:

123-86-4 N-butyl acetate

Oral	LD50	13,100 mg/kg bw (rat)
Dermal	LD50	>5,000 mg/kg bw (rabbit)
Inhalative	LC50/4 h	>21 mg/l (rat)

110-43-0 Heptan-2-one

Oral	LD50	1,670 mg/kg bw (rat)
Dermal	LD50	12,600 mg/kg bw (rabbit)
	Short-term exposure (15 minutes): 100 ppm	475 mg/m ³ (Occupational exposure limits)

97-86-9 Isobutyl methacrylate

Oral	LD50	11,990 mg/kg bw (mouse)
------	------	-------------------------

868-77-9 2-hydroxyethyl methacrylate

Oral	LD50	5,050 mg/kg bw (rat)
------	------	----------------------

80-62-6 Methyl methacrylate

Oral	LD50	7,872 mg/kg bw (rat)
Dermal	Acute / short-term - local effects.	1.5 mg/cm ² (Employees)
	Long-term - local effects.	1.5 mg/cm ² (Employees)

- Respiratory or skin sensitisation May cause an allergic skin reaction.
- STOT-single exposure May cause drowsiness or dizziness.
- 11.2 Information on other hazards

- Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.
- 12.6 Endocrine disrupting properties
The product does not contain substances with endocrine disrupting properties.

(Contd. on page 14)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 05.01.2024

Version number 19 (replaces version 18)

Revision: 05.01.2024

Trade name: Epifanes PU Speedcoat Comp. A

(Contd. of page 13)

- 12.7 Other adverse effects
- Remark: Harmful to fish
- Additional ecological information:
- General notes:
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Harmful to aquatic organisms

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods
- Recommendation
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.
- Recommended cleansing agents:
Water, if necessary together with cleansing agents.

SECTION 14: Transport information

- 14.1 UN number or ID number
- ADR, IMDG, IATA UN1263
- 14.2 UN proper shipping name
- ADR 1263 PAINT
- IMDG, IATA PAINT
- 14.3 Transport hazard class(es)
- ADR
- 
- Class 3 (F1) Flammable liquids.
- Label 3
- IMDG, IATA
- 
- Class 3 Flammable liquids.

(Contd. on page 15)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 05.01.2024

Version number 19 (replaces version 18)

Revision: 05.01.2024

Trade name: Epifanes PU Speedcoat Comp. A

(Contd. of page 14)

· Label	3
· 14.4 Packing group	
· ADR, IMDG, IATA	III
· 14.5 Environmental hazards:	Not applicable.
· 14.6 Special precautions for user	Warning: Flammable liquids.
· Hazard identification number (Kemler code):	30
· EMS Number:	F-E, <u>S-E</u>
· Stowage Category	A
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
· Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Poisons Act

- Regulated explosives precursors

None of the ingredients is listed.

- Regulated poisons

None of the ingredients is listed.

- Reportable explosives precursors

None of the ingredients is listed.

(Contd. on page 16)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 05.01.2024

Version number 19 (replaces version 18)

Revision: 05.01.2024

Trade name: Epifanes PU Speedcoat Comp. A

(Contd. of page 15)

· Reportable poisons

None of the ingredients is listed.

- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements
5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements
50,000 t
- National regulations:
- Technical instructions (air):

Class	Share in %
NK	25-50

- Waterhazard class:
Water hazard class 1 (Self-assessment): slightly hazardous for water.
- 15.2 Chemical safety assessment:
A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases
 - H225 Highly flammable liquid and vapour.
 - H226 Flammable liquid and vapour.
 - H302 Harmful if swallowed.
 - H304 May be fatal if swallowed and enters airways.
 - H315 Causes skin irritation.
 - H317 May cause an allergic skin reaction.
 - H319 Causes serious eye irritation.
 - H332 Harmful if inhaled.
 - H335 May cause respiratory irritation.
 - H336 May cause drowsiness or dizziness.
 - H361f Suspected of damaging fertility.
 - H400 Very toxic to aquatic life.
 - H410 Very toxic to aquatic life with long lasting effects.
 - H411 Toxic to aquatic life with long lasting effects.
 - EUH066 Repeated exposure may cause skin dryness or cracking.
- Department issuing SDS: Research & Development.
- Contact: J.J. van Dijk, tel: +31 297 360678, email: rend@epifanes.nl
- Abbreviations and acronyms:
 - ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 - IMDG: International Maritime Code for Dangerous Goods

(Contd. on page 17)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 05.01.2024

Version number 19 (replaces version 18)

Revision: 05.01.2024

Trade name: Epifanes PU Speedcoat Comp. A

(Contd. of page 16)

IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
DNEL: Derived No-Effect Level (UK REACH)
PNEC: Predicted No-Effect Concentration (UK REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
ATE: Acute toxicity estimate values
Flam. Liq. 2: Flammable liquids - Category 2
Flam. Liq. 3: Flammable liquids - Category 3
Acute Tox. 4: Acute toxicity - Category 4
Skin Irrit. 2: Skin corrosion/irritation - Category 2
Eye Irrit. 2: Serious eye damage/eye irritation - Category 2
Skin Sens. 1: Skin sensitisation - Category 1
Skin Sens. 1A: Skin sensitisation - Category 1A
Skin Sens. 1B: Skin sensitisation - Category 1B
Repr. 2: Reproductive toxicity - Category 2
STOT SE 3: Specific target organ toxicity (single exposure) - Category 3
Asp. Tox. 1: Aspiration hazard - Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3
* Data compared to the previous version altered.

GB