

Epifanes Fiberglass Prep Cleaner

Highly effective degreaser for GPR / Fiberglass

Type	Mixture of acetate and hydrocarbon
Properties	<p>A special high performing degreaser for optimum preparation of fibre-glass surfaces. Removes all wax and oily residues on gelcoat and ensures a proper surface for sanding and coating.</p> <p>Also suited for cleaning bare steel, alloy and epoxy resin. Perfectly removes all wax, fiberglass agents oil, grease, tar or any other contamination.</p>
Recommended use	<p>Fiberglass/GRP : cleaning and degreaser of fiberglass surfaces above and below the waterline.</p> <p>Always use multiple clean lintfree rags or paper towels. Wipe surface with a cloth soaked with Epifanes Fiberglass Prep Cleaner. Continue by wiping the surface with a clean second dry cloth. Turn rag/towel constantly during degreasing and often renew rag/towel. This will ensure that contamination is actually removed and not replaced.</p> <p>Degreasing must be executed before sanding in order to avoid sanding the way substance into the sand marks.</p> <p>Epifanes Fiberglass Prep Cleaner is not suited for degreasing one-component paint or varnish systems.</p>
Density	0.97 kg/dm ³
VOC - level	344 gr./liter
Packing	1000ml. - 5000ml.
Shelf life	In closed container stored in a dark and dry location between 41-77°F: 3 years
Safety	<p>This product is flammable and harmful when inhaled. Avoid breathing vapor. Skin and eye irritant. Avoid contact with eyes and prolonged and repeated contact with skin. In case of eye contact, flush thoroughly with tap water for at least 15 minutes and get immediate medical attention. Keep away from heat and open flame. Use only with adequate ventilation. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Store in a cool well ventilated area. Do not empty into drains. Close container after each use.</p>
Safety precautions	<p>Eyes : Use suitable protective glasses Skin : Use protective clothing and gloves Breathing: Use appropriate breathing apparatus</p> <p>Also see MSDS</p>

Although the facts and suggestions in this product information sheet are based on our own research and field experiences and are believed reliable, we cannot simply be held responsible for performance or results obtained through the use of this product. Ineffectiveness or other unintended consequences may result, because of such factors as weather, conditions, presence or other materials or the manner of preparation, use or application all of which are beyond W. Heeren & Zoon's control. All such risks are assumed by user.

DISCLAIMER OF WARRANTIES. Seller makes no express warranties. THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE EXCLUDED. In the event a warranty is created by law, buyer's EXCLUSIVE REMEDY shall be the replacement of any defective product. No other remedy (including, but not limited to, incidental or consequential damages for lost profits, lost sales, injury to person or property, or any other incidental or consequential loss) shall be available to buyer.