

MATERIAL SAFETY DATA SHEET

Sales Order: {SalesOrd}

Wash Primer CF Base

MSDS Revision No: E1 -2
MSDS Revision Date: 31/01/2011



Akzo Nobel Coatings
Interlux Yacht Finishes
2270 Morris Avenue
P. O. Box 386
Union, NJ 07083

EMERGENCY NUMBERS:

(800) 424-9300 CHEMTREC (USA)
(703) 527-3887 CHEMTREC (Intl)
(800) 854-6813 Poison Control Center
CUSTOMER SERVICE: (Non-Emergency)
(800) 589-1267 International Paint
(800) 631-7481 Interlux

1. GENERAL INFORMATION

Product Identity: Wash Primer CF Base

Bulk Sales Reference No: OD6600

IMPORTANT: Read this MSDS before handling or disposing of this product, and provide this information to the employee, customers, and users of this product. PLEASE NOTE THE MSDS REVISION NUMBER AT THE TOP OF THIS PAGE. If the MSDS Revision Number posted at the top of this page does not match the MSDS Revision Number on the product label, please contact Customer Service at the phone number included above for the correct MSDS. This product is covered by the OSHA Hazard Communication Standard and this document has been prepared in accordance with requirements of this standard.

NOTICE: OSHA hazardous chemicals are listed in Section 2 if present at 1% or more. Carcinogens and extraordinarily/special hazardous chemicals are listed in Section 2 if present at .1% or more. Additional regulatory information for specific chemical categories is included in Section 15.

2. HAZARDOUS INGREDIENT INFORMATION

| CAS No. | Ingredient Name & % | Source | Exposure Data |
|--------------|--|------------|--|
| 0000095-63-6 | 1,2,4-Trimethyl benzene 1.0 - 10% by Weight | OSHA: | No Established Limit |
| | | ACGIH: | No Established Limit |
| | | NIOSH: | 25 ppm TWA; 125 mg/m3 TWA |
| | | Supplier: | No Established Limit |
| | | OHSA, CAN: | No Established Limit |
| | | Mexico: | No Established Limit |
| | | Brazil: | No Established Limit |
| | | Source | Health Data |
| | | NIOSH: | No Established Limit |
| | | Source | Carcinogen Data |
| | | OSHA: | Select Carcinogen: No |
| | | NTP: | Known Carcinogen: No; Suspected Carcinogen: No |
| | | IARC: | Group 1: No; Group 2A: No; Group 2b: No; Group 3: No; Group 4: No |

| CAS No. | Ingredient Name & % | Source | Exposure Data |
|--------------|--|------------|--|
| 0000100-41-4 | Benzene, ethyl- 1.0 - 10% by Weight | OSHA: | 100 ppm TWA; 435 mg/m3 TWA125 ppm STEL; 545 mg/m3 STEL |
| | | ACGIH: | 100 ppm TWA125 ppm STEL |
| | | NIOSH: | 100 ppm TWA; 435 mg/m3 TWA125 ppm STEL; 545 mg/m3 STEL800 ppm IDLH (10% LEL) |
| | | Supplier: | No Established Limit |
| | | OHSA, CAN: | 100 ppm TWAEV; 435 mg/m3 TWAEV125 ppm STEV; 540 mg/m3 STEV |
| | | Mexico: | 100 ppm TWA; 435 mg/m3 TWA125 ppm STEL; 545 mg/m3 STEL |
| | | Brazil: | 78 ppm TWA; 340 mg/m3 TWA |
| | | Source | Health Data |
| | | NIOSH: | Eye skin |
| | | Source | Carcinogen Data |
| | | OSHA: | Select Carcinogen: Yes |
| | | NTP: | Known Carcinogen: No; Suspected Carcinogen: No |

OD6600_E1

IARC: Group 1: No; Group 2A: No; Group 2b: Yes; Group 3: No; Group 4: No

| CAS No. | Ingredient Name & % | Source | Exposure Data |
|--------------|---|------------|---|
| 0000107-98-2 | Propylene glycol monomethyl ether 25 – 50% by Weight | OSHA: | 150 ppm STEL; 540 mg/m3 STEL |
| | | ACGIH: | 100 ppm TWA150 ppm STEL |
| | | NIOSH: | 100 ppm TWA; 360 mg/m3 TWA150 ppm STEL; 540 mg/m3 STEL |
| | | Supplier: | No Established Limit |
| | | OHSA, CAN: | 100 ppm TWAEV; 365 mg/m3 TWAEV150 ppm STEV; 550 mg/m3 STEV |
| | | Mexico: | No Established Limit |
| | | Brazil: | No Established Limit |
| | | Source | Health Data |
| | | NIOSH: | Eye nose |
| | | Source | Carcinogen Data |
| | | OSHA: | Select Carcinogen: No |
| | | NTP: | Known Carcinogen: No; Suspected Carcinogen: No |
| | | IARC: | Group 1: No; Group 2A: No; Group 2b: No; Group 3: No; Group 4: No |

| CAS No. | Ingredient Name & % | Source | Exposure Data |
|--------------|---|------------|---|
| 0000108-67-8 | 1,3,5-Trimethylbenzene 1.0 – 10% by Weight | OSHA: | No Established Limit |
| | | ACGIH: | No Established Limit |
| | | NIOSH: | 25 ppm TWA; 125 mg/m3 TWA |
| | | Supplier: | No Established Limit |
| | | OHSA, CAN: | No Established Limit |
| | | Mexico: | No Established Limit |
| | | Brazil: | No Established Limit |
| | | Source | Health Data |
| | | NIOSH: | No Established Limit |
| | | Source | Carcinogen Data |
| | | OSHA: | Select Carcinogen: No |
| | | NTP: | Known Carcinogen: No; Suspected Carcinogen: No |
| | | IARC: | Group 1: No; Group 2A: No; Group 2b: No; Group 3: No; Group 4: No |

| CAS No. | Ingredient Name & % | Source | Exposure Data |
|--------------|--|------------|---|
| 0001305-62-0 | Calcium hydroxide 1.0 – 10% by Weight | OSHA: | 15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction) |
| | | ACGIH: | 5 mg/m3 TWA |
| | | NIOSH: | 5 mg/m3 TWA |
| | | Supplier: | No Established Limit |
| | | OHSA, CAN: | 5 mg/m3 TWAEV |
| | | Mexico: | 5 mg/m3 TWA |
| | | Brazil: | No Established Limit |
| | | Source | Health Data |
| | | NIOSH: | Caustic irritation of all exposed body surfaces and the respiratory tract |
| | | Source | Carcinogen Data |
| | | OSHA: | Select Carcinogen: No |
| | | NTP: | Known Carcinogen: No; Suspected Carcinogen: No |
| | | IARC: | Group 1: No; Group 2A: No; Group 2b: No; Group 3: No; Group 4: No |

| CAS No. | Ingredient Name & % | Source | Exposure Data |
|---------|---------------------|--------|--|
| | | OSHA: | 100 ppm TWA; 435 mg/m3 TWA150 ppm STEL; 655 mg/m3 STEL |
| | | ACGIH: | 100 ppm TWA150 ppm STEL |

0001330-20-7 Xylenes (o-, m-, p- isomers)
1.0 – 10% by Weight

OD6600_E1

| | | |
|--|------------|--|
| | NIOSH: | No Established Limit |
| | Supplier: | No Established Limit |
| | OHSA, CAN: | 100 ppm TWAEV; 435 mg/m3 TWAEV/150 ppm STEV; 650 mg/m3 STEV |
| | Mexico: | 100 ppm TWA; 435 mg/m3 TWA/150 ppm STEL; 655 mg/m3 STEL |
| | Brazil: | 78 ppm TWA; 340 mg/m3 TWA |
| | Source | Health Data |
| | NIOSH: | Central nervous system depressant; respiratory and eye irritation |
| | Source | Carcinogen Data |
| | OSHA: | Select Carcinogen: No |
| | NTP: | Known Carcinogen: No; Suspected Carcinogen: No |
| | IARC: | Group 1: No; Group 2A: No; Group 2b: No; Group 3: Yes; Group 4: No |

| CAS No. | Ingredient Name & % | Source | Exposure Data |
|--------------|--|------------|--|
| 0007631-86-9 | Silica, amorphous 1.0 – 10% by Weight | OSHA: | No Established Limit |
| | | ACGIH: | No Established Limit |
| | | NIOSH: | 6 mg/m3 TWA/3000 mg/m3 IDLH |
| | | Supplier: | No Established Limit |
| | | OHSA, CAN: | No Established Limit |
| | | Mexico: | No Established Limit |
| | | Brazil: | No Established Limit |
| | | Source | Health Data |
| | | NIOSH: | No Established Limit |
| | | Source | Carcinogen Data |
| | | OSHA: | Select Carcinogen: No |
| | | NTP: | Known Carcinogen: No; Suspected Carcinogen: No |
| | | IARC: | Group 1: No; Group 2A: No; Group 2b: No; Group 3: Yes; Group 4: No |

| CAS No. | Ingredient Name & % | Source | Exposure Data |
|--------------|---|------------|--|
| 0013463-67-7 | Titanium dioxide 1.0 – 10% by Weight | OSHA: | 15 mg/m3 TWA (total dust) |
| | | ACGIH: | 10 mg/m3 TWA |
| | | NIOSH: | 5000 mg/m3 IDLH |
| | | Supplier: | No Established Limit |
| | | OHSA, CAN: | 10 mg/m3 TWAEV (total dust) |
| | | Mexico: | 10 mg/m3 TWA (as Ti)/20 mg/m3 STEL (as Ti) |
| | | Brazil: | No Established Limit |
| | | Source | Health Data |
| | | NIOSH: | Lung tumors in animals |
| | | Source | Carcinogen Data |
| | | OSHA: | Select Carcinogen: Yes |
| | | NTP: | Known Carcinogen: No; Suspected Carcinogen: No |
| | | IARC: | Group 1: No; Group 2A: No; Group 2b: Yes; Group 3: No; Group 4: No |

| CAS No. | Ingredient Name & % | Source | Exposure Data |
|--------------|-----------------------------|------------|--|
| 0014807-96-6 | Talc 1.0 – 10% by Weight | OSHA: | No Established Limit |
| | | ACGIH: | 2 mg/m3 TWA (respirable fraction, particulate matter with no asbestos and less than 1% crystalline) |
| | | NIOSH: | 2 mg/m3 TWA (respirable dust, containing no asbestos and less than 1% quartz)/1000 mg/m3 IDLH (containing no asbestos and less than 1% quartz) |
| | | Supplier: | No Established Limit |
| | | OHSA, CAN: | 2 mg/m3 TWAEV (respirable, containing no asbestos and less than 1% crystalline silica) |

OD6600_E1

| | |
|---------|--|
| Mexico: | 2 mg/m3 TWA |
| Brazil: | No Established Limit |
| Source | Health Data |
| NIOSH: | (containing asbestos); Fibrotic pneumoconiosis; (containing no asbestos); Nonmalignant respiratory effects |
| Source | Carcinogen Data |
| OSHA: | Select Carcinogen: No |
| NTP: | Known Carcinogen: No; Suspected Carcinogen: No |
| IARC: | Group 1: No; Group 2A: No; Group 2b: No; Group 3: Yes; Group 4: No |

| CAS No. | Ingredient Name & % | Source | Exposure Data |
|--------------|--|-----------|---|
| 0025068-38-6 | Bisphenol A – Epichlorohydrin polymer 1.0 – 10% by Weight | OSHA: | No Established Limit |
| | | ACGIH: | No Established Limit |
| | | NIOSH: | No Established Limit |
| | | Supplier: | No Established Limit |
| | | OHS, CAN: | No Established Limit |
| | | Mexico: | No Established Limit |
| | | Brazil: | No Established Limit |
| | | Source | Health Data |
| | | NIOSH: | No Established Limit |
| | | Source | Carcinogen Data |
| | | OSHA: | Select Carcinogen: No |
| | | NTP: | Known Carcinogen: No; Suspected Carcinogen: No |
| | | IARC: | Group 1: No; Group 2A: No; Group 2b: No; Group 3: No; Group 4: No |

| CAS No. | Ingredient Name & % | Source | Exposure Data |
|--------------|--|-----------|---|
| 0064742-95-6 | Petroleum naphtha, light aromatic 1.0 – 10% by Weight | OSHA: | No Established Limit |
| | | ACGIH: | No Established Limit |
| | | NIOSH: | No Established Limit |
| | | Supplier: | No Established Limit |
| | | OHS, CAN: | No Established Limit |
| | | Mexico: | No Established Limit |
| | | Brazil: | No Established Limit |
| | | Source | Health Data |
| | | NIOSH: | No Established Limit |
| | | Source | Carcinogen Data |
| | | OSHA: | Select Carcinogen: No |
| | | NTP: | Known Carcinogen: No; Suspected Carcinogen: No |
| | | IARC: | Group 1: No; Group 2A: No; Group 2b: No; Group 3: No; Group 4: No |

3. HAZARD IDENTIFICATION

| | |
|------------------|--|
| Overview: | NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid contact with eyes, skin and clothing. |
| Inhalation: | Harmful if inhaled. Causes nose and throat irritation. Vapors may affect the brain or nervous system causing dizziness, headache or nausea. |
| Eyes: | Risk of serious damage to eyes. Do not get in eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 2 of this document. Depending on the site-specific condition of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use. |
| Skin: | Causes skin irritation. May cause delayed skin irritation. May be harmful if absorbed through the skin. |
| Ingestion: | Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or drowsiness. |
| Chronic Effects: | Birth defect hazard. Contains an ingredient which can cause birth defects (See Section 2 and Section 15 for each ingredient). Possible cancer hazard. Contains an ingredient which may cause cancer based on animal data (See |

OD6600_E1

Section 2 and Section 15 for each ingredient). Risk of cancer depends on duration and level of exposure.

| | | | |
|--------------|------------|-----------------|---------------|
| HMIS Rating: | Health: 2* | Flammability: 3 | Reactivity: 0 |
|--------------|------------|-----------------|---------------|

4. FIRST AID MEASURES

| | |
|-------------|---|
| General: | Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean or destroy contaminated shoes. |
| Inhalation: | If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately. |
| Eyes: | In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately. |
| Skin: | In case of contact, immediately flush skin with soap and plenty of water. Get medical attention immediately. |
| Ingestion: | If swallowed, immediately contact Poison Control Center at 1-800-854-6813. DO NOT induce vomiting unless instructed to do so by medical personnel. Never give anything by mouth to an unconscious person. |

5. PROTECTIVE EQUIPMENT AND CONTROL MEASURES

| | |
|-----------------------|---|
| Respiratory: | Select equipment to provide protection from the ingredients listed in Section 2 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1-800-243-4630, in Canada call 1-800-267-4414. Please do not contact these numbers regarding other manufacturer's respiratory protection products. 3M does not endorse the accuracy of the information contained in this Material Safety Data Sheet. |
| Eyes: | Do not get in eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 2 of this document. Depending on the site-specific condition of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 2 of this document. Depending on the site-specific conditions of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use. |
| Skin/Hand: | Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 2 of this document. Depending on the site-specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use. |
| Engineering Controls: | Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. |
| Other Work Practices: | Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of soap and water. |

6. FIRE AND EXPLOSION INFORMATION

| | |
|------------------------------|---|
| Flash Point: | F: 80 C: 27 |
| Lower Explosive Limit (LEL): | 1.6 (%vol in air) at Normal Atmospheric Temp and Pressure |
| Fire and Explosion Hazards: | Flammable liquid and vapor. FLAMMABLE/COMBUSTIBLE MATERIALS: Will be easily ignited by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks) creating a vapor explosion hazard. Runoff to sewers may create fire or explosion hazard. Containers may explode when heated. |
| Fire Fighting Procedures: | CAUTION: This product has a very low flashpoint. Use of water spray when fighting fire may be inefficient. SMALL FIRES: Use dry chemical, CO ₂ , water spray or alcohol-resistant foam. LARGE FIRES: Use water spray, fog, or alcohol-resistant foam. Do not use straight streams. Move containers from fire area if you can do so without risk. Runoff from fire control may cause pollution. Dike fire control water for later disposal. Do not scatter the material. Also Reference Emergency Response Guide Number: 127 |

7. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|-----------------|---------------|
| Physical State: | Liquid Yellow |
|-----------------|---------------|

OD6600_E1

| | |
|--|---|
| pH: | No Established Limit |
| Specific Gravity: | 1.11754 |
| Boiling Point (F): | 243 |
| Vapor Density: | Heavier than air |
| VOC Content (lbs): | Refer to the Technical Data Sheet for this product. |
| Evaporation Rate: | Slower than ether |
| VOHAP content (gm/litre of paint): | 125.84 (as supplied) |
| VOHAP content (gm/litre of Solid Coating): | 511.36 (as supplied) |

8. STABILITY AND REACTIVITY DATA

| | |
|--------------------------|--|
| General: | This product is stable and hazardous polymerization will not occur. Not sensitive to mechanical impact. Excessive heat and fumes generation can occur if improperly handled. |
| Incompatible Materials: | Strong oxidizing agents. |
| Hazardous Decomposition: | May produce hazardous fumes when heated to decomposition as in welding. Fumes may produce Carbon Dioxide and Carbon Monoxide. |

9. HANDLING AND STORAGE

| | |
|-----------------------------------|--|
| Storage Temperature: | Store between 40–100F (4–38C). |
| Handling and Storage Precautions: | Keep away from heat, sparks and flame. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Vapors may cause flash fire or ignite explosively. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. Do not get in eyes, on skin or clothing. Close container after each use. Wash thoroughly after handling. |

10. TOXICOLOGICAL DATA

| | |
|----------|---|
| General: | NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. No additional information provided for this product. See Section 2 for chemical specific data. |
|----------|---|

11. ECOLOGICAL DATA

| | |
|----------|--|
| General: | Not Defined No additional information provided for this product. See Section 2 for chemical specific data. |
|----------|--|

12. ACCIDENTAL RELEASE MEASURES

| | |
|----------------------------|---|
| Spill Response Procedures: | ELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area). Use only non-sparking equipment to handle spilled material and absorbent. Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to containers. Use non-sparking tools to collect absorbed material. |
| Public Safety: | CALL CHEMTREC at (800)–424–9300 for emergency response. Isolate spill or leak area immediately for at least 25 to 50 meters (80 to 160 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. LARGE SPILLS: Consider initial downwind evacuation for at least 300 meters (1000 feet). Also, Reference Emergency Response Guide Number: 127 |

13. DISPOSAL CONSIDERATION

| | |
|-----------------|--|
| Waste Disposal: | Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Section 15 if listed). |
|-----------------|--|

14. TRANSPORTATION INFORMATION

| DOT (Domestic Surface Transportation) | | IMO / IMDG (Ocean Transportation) | |
|---------------------------------------|----------------------|-------------------------------------|--------------------------------------|
| DOT Proper Shipping Name: PAINT | | IMDG Proper Shipping Name: PAINT | |
| DOT Hazard Class: | 3 | IMDG Hazard Class: | 3 – Flammable and Combustible liquid |
| UN / NA Number: | UN 1263 | UN Number: | UN 1263 |
| DOT Packing Group: | III | IMDG Packing Group: | III |
| CERCLA/DOT RQ: | 116 gal. / 1077 lbs. | System Reference Code: | 1 |

15. REGULATORY INFORMATION

| | |
|---|--|
| Regulatory Overview: | The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be listed on the TSCA Inventory. Note: Any chemical ingredients listed in Section 15, that do not also appear in Section 2, are contained in the product at a concentration below the applicable OSHA threshold level of 1% or 0.1%. |
| WHMIS Classification: | No Established Limit |
| Regulatory List | Product Ingredients on List |
| DOT Marine Pollutants (10%): (No Product Ingredients Listed) | |
| DOT Severe Marine Pollutants (1%): (No Product Ingredients Listed) | |
| EPCRA 311/312 Chemicals and RQs (>.1%) : | |
| 0000098–82–8 | Cumene : 5000 lb final RQ; 2270 kg final RQ |
| 0000100–41–4 | Benzene, ethyl– : 1000 lb final RQ; 454 kg final RQ |
| 0001330–20–7 | Xylenes (o–, m–, p– isomers) : 100 lb final RQ; 45.4 kg final RQ |
| EPCRA 302 Extremely Hazardous (>.1%) : | |
| (No Product Ingredients Listed) | |
| EPCRA 313 Toxic Chemicals (>.1%) : | |
| 0000095–63–6 | 1,2,4–Trimethyl benzene |
| 0001344–28–1 | Aluminum oxide |
| 0000098–82–8 | Cumene |
| 0000100–41–4 | Benzene, ethyl– |
| 0001330–20–7 | Xylenes (o–, m–, p– isomers) |
| Mass RTK Substances (>1%) : | |
| 0000095–63–6 | 1,2,4–Trimethyl benzene |
| 0001305–62–0 | Calcium hydroxide |
| 0000100–41–4 | Benzene, ethyl– |
| 0000107–98–2 | Propylene glycol monomethyl ether |
| 0007631–86–9 | Silica, amorphous |
| 0014807–96–6 | Talc |
| 0013463–67–7 | Titanium dioxide |
| 0000108–67–8 | 1,3,5–Trimethylbenzene |
| 0001330–20–7 | Xylenes (o–, m–, p– isomers) |
| Mass Extraordinarily Haz Sub (>.01%) : | |
| 0014808–60–7 | Quartz |
| 0014464–46–1 | Silica, cristobalite |
| Penn RTK Substances (>1%) : | |
| 0000095–63–6 | 1,2,4–Trimethyl benzene |
| 0001305–62–0 | Calcium hydroxide |
| 0000100–41–4 | Benzene, ethyl– |
| 0000107–98–2 | Propylene glycol monomethyl ether |

| | |
|--|-----------------------------------|
| 0007631-86-9 | Silica, amorphous |
| 0014807-96-6 | Talc |
| 0013463-67-7 | Titanium dioxide |
| 0001330-20-7 | Xylenes (o-, m-, p- isomers) |
| Penn Special Hazardous Substances (>.01%) : | |
| (No Product Ingredients Listed) | |
| Rhode Island Hazardous Substances (>.1%) : | |
| 0001344-28-1 | Aluminum oxide |
| 0001305-62-0 | Calcium hydroxide |
| 0000098-82-8 | Cumene |
| 0000100-41-4 | Benzene, ethyl- |
| 0000107-98-2 | Propylene glycol monomethyl ether |
| 0014807-96-6 | Talc |
| 0013463-67-7 | Titanium dioxide |
| 0001330-20-7 | Xylenes (o-, m-, p- isomers) |
| RCRA Status (%): | |
| 0007440-38-2 | Arsenic : .00005 |
| 0007440-47-3 | Chromium : .00073 |
| N.J. RTK Substances (>1%) : | |
| 0000095-63-6 | 1,2,4-Trimethyl benzene |
| 0001305-62-0 | Calcium hydroxide |
| 0000100-41-4 | Benzene, ethyl- |
| 0000107-98-2 | Propylene glycol monomethyl ether |
| 0007631-86-9 | Silica, amorphous |
| 0014807-96-6 | Talc |
| 0013463-67-7 | Titanium dioxide |
| 0000108-67-8 | 1,3,5-Trimethylbenzene |
| 0001330-20-7 | Xylenes (o-, m-, p- isomers) |
| N.J. Special Hazardous Substances (>.01%) : | |
| 0000100-41-4 | Benzene, ethyl- |
| 0001330-20-7 | Xylenes (o-, m-, p- isomers) |
| N.J. Env. Hazardous Substances (>.1%) : | |
| 0000095-63-6 | 1,2,4-Trimethyl benzene |
| 0001344-28-1 | Aluminum oxide |
| 0000098-82-8 | Cumene |
| 0000100-41-4 | Benzene, ethyl- |
| 0001330-20-7 | Xylenes (o-, m-, p- isomers) |
| Proposition 65 – Carcinogens (>0%): | |
| 0000100-41-4 | Benzene, ethyl- |
| 0007440-02-0 | Nickel |
| 0014808-60-7 | Quartz |
| Proposition 65 – Female Repro Toxins (>0%): | |
| (No Product Ingredients Listed) | |
| Proposition 65 – Male Repro Toxins (>0%): | |
| (No Product Ingredients Listed) | |
| Proposition 65 – Developmental Toxins (>0%): | |
| (No Product Ingredients Listed) | |

16. OTHER INFORMATION

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

FOR PROFESSIONAL USE ONLY

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.

Head Office

International Paint, LLC, 6001 Antoine Drive, Houston, Texas 77091. <http://www.international-pc.com> or <http://www.international-marine.com>

End Of Document

MATERIAL SAFETY DATA SHEET

Sales Order: {SalesOrd}

Wash Primer CF Converter

MSDS Revision No: E2 -2
MSDS Revision Date: 11/04/2011



Akzo Nobel Coatings
International Paint LLC
2270 Morris Avenue
P. O. Box 386
Union, NJ 07083

EMERGENCY NUMBERS:

| | |
|----------------------------------|-------------------------------------|
| (800) 424-9300 | CHEMTREC (USA) |
| (703) 527-3887 | CHEMTREC (Intl) |
| (800) 854-6813 | Poison Control Center |
| CUSTOMER SERVICE: (800) 589-1267 | (Non-Emergency) International Paint |
| (800) 631-7481 | Interlux |

1. GENERAL INFORMATION

Product Identity: Wash Primer CF Converter

Bulk Sales Reference No: OD3300

IMPORTANT: Read this MSDS before handling or disposing of this product, and provide this information to the employee, customers, and users of this product. PLEASE NOTE THE MSDS REVISION NUMBER AT THE TOP OF THIS PAGE. If the MSDS Revision Number posted at the top of this page does not match the MSDS Revision Number on the product label, please contact Customer Service at the phone number included above for the correct MSDS. This product is covered by the OSHA Hazard Communication Standard and this document has been prepared in accordance with requirements of this standard.

NOTICE: OSHA hazardous chemicals are listed in Section 2 if present at 1% or more. Carcinogens and extraordinarily/special hazardous chemicals are listed in Section 2 if present at .1% or more. Additional regulatory information for specific chemical categories is included in Section 15.

2. HAZARDOUS INGREDIENT INFORMATION

| CAS No. | Ingredient Name & % | Source | Exposure Data |
|--------------|--|------------|---|
| 0000107-98-2 | Propylene glycol monomethyl ether 75 - 100% by Weight | OSHA: | 150 ppm STEL; 540 mg/m3 STEL |
| | | ACGIH: | 100 ppm TWA/150 ppm STEL |
| | | NIOSH: | 100 ppm TWA; 360 mg/m3 TWA/150 ppm STEL; 540 mg/m3 STEL |
| | | Supplier: | No Established Limit |
| | | OHSA, CAN: | 100 ppm TWA/150 ppm STEL |
| | | Mexico: | No Established Limit |
| | | Brazil: | No Established Limit |
| | | Source | Health Data |
| | | NIOSH: | Eye nose |
| | | Source | Carcinogen Data |
| | | OSHA: | Select Carcinogen: No |
| | | NTP: | Known Carcinogen: No; Suspected Carcinogen: No |
| | | IARC: | Group 1: No; Group 2A: No; Group 2b: No; Group 3: No; Group 4: No |

| CAS No. | Ingredient Name & % | Source | Exposure Data |
|--------------|---|------------|---|
| 0001589-47-5 | 2-Methoxy-1-propanol 1.0 - 10% by Weight | OSHA: | No Established Limit |
| | | ACGIH: | No Established Limit |
| | | NIOSH: | No Established Limit |
| | | Supplier: | No Established Limit |
| | | OHSA, CAN: | No Established Limit |
| | | Mexico: | No Established Limit |
| | | Brazil: | No Established Limit |
| | | Source | Health Data |
| | | NIOSH: | No Established Limit |
| | | Source | Carcinogen Data |
| | | OSHA: | Select Carcinogen: No |
| | | NTP: | Known Carcinogen: No; Suspected Carcinogen: No |
| | | IARC: | Group 1: No; Group 2A: No; Group 2b: No; Group 3: No; Group 4: No |

3. HAZARD IDENTIFICATION

| | | | |
|------------------|--|-----------------|---------------|
| Overview: | NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid contact with eyes, skin and clothing. | | |
| Inhalation: | Harmful if inhaled. Causes nose and throat irritation. Vapors may affect the brain or nervous system causing dizziness, headache or nausea. | | |
| Eyes: | Causes severe eye irritation. Avoid contact with eyes. | | |
| Skin: | Causes skin irritation. May be harmful if absorbed through the skin. | | |
| Ingestion: | Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or drowsiness. | | |
| Chronic Effects: | Birth defect hazard. Contains an ingredient which can cause birth defects (See Section 2 and Section 15 for each ingredient). | | |
| HMIS Rating: | Health: 2* | Flammability: 3 | Reactivity: 0 |

4. FIRST AID MEASURES

| | |
|-------------|---|
| General: | Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean or destroy contaminated shoes. |
| Inhalation: | If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately. |
| Eyes: | In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately. |
| Skin: | In case of contact, immediately flush skin with soap and plenty of water. Get medical attention immediately. |
| Ingestion: | If swallowed, immediately contact Poison Control Center at 1-800-854-6813. DO NOT induce vomiting unless instructed to do so by medical personnel. Never give anything by mouth to an unconscious person. |

5. PROTECTIVE EQUIPMENT AND CONTROL MEASURES

| | |
|-----------------------|---|
| Respiratory: | Select equipment to provide protection from the ingredients listed in Section 2 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1-800-243-4630, in Canada call 1-800-267-4414. Please do not contact these numbers regarding other manufacturer's respiratory protection products. 3M does not endorse the accuracy of the information contained in this Material Safety Data Sheet. |
| Eyes: | Avoid contact with eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 2 of this document. Depending on the site-specific conditions of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use. |
| Skin/Hand: | Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 2 of this document. Depending on the site-specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use. |
| Engineering Controls: | Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. |
| Other Work Practices: | Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of soap and water. |

6. FIRE AND EXPLOSION INFORMATION

| | |
|------------------------------|--|
| Flash Point: | F: 89 C: 32 |
| Lower Explosive Limit (LEL): | 1.6 (%vol in air) at Normal Atmospheric Temp and Pressure |
| Fire and Explosion Hazards: | Flammable liquid and vapor. HIGHLY FLAMMABLE MATERIALS: Will be easily ignited by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks) creating a vapor explosion hazard. Runoff to sewers may create fire or explosion hazard. Containers may explode when heated. Many liquids are lighter than water. |

OD3300_E2

CAUTION: This product has a very low flashpoint. Use of water spray when fighting fire may be inefficient.
CAUTION: For mixtures containing alcohol or polar solvent, alcohol-resistant foam may be more effective.
Fire Fighting Procedures: SMALL FIRES: Use dry chemical, CO₂, water spray or regular foam. LARGE FIRES: Use water spray, fog, or regular foam. Do not use straight streams. Move containers from fire area if you can do so without risk.
Also Reference Emergency Response Guide Number: 128

7. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|--|---|
| Physical State: | Liquid Colourless |
| pH: | No Established Limit |
| Specific Gravity: | 0.919637 |
| Boiling Point (F): | 243 |
| Vapor Density: | Heavier than air |
| VOC Content (lbs): | Refer to the Technical Data Sheet for this product. |
| Evaporation Rate: | Slower than ether |
| VOHAP content (gm/litre of paint): | 0.00 (as supplied) |
| VOHAP content (gm/litre of Solid Coating): | 0.00 (as supplied) |

8. STABILITY AND REACTIVITY DATA

| | |
|--------------------------|--|
| General: | This product is stable and hazardous polymerization will not occur. Not sensitive to mechanical impact. Excessive heat and fumes generation can occur if improperly handled. |
| Incompatible Materials: | Strong oxidizing agents. |
| Hazardous Decomposition: | May produce hazardous fumes when heated to decomposition as in welding. Fumes may produce Carbon Dioxide and Carbon Monoxide. |

9. HANDLING AND STORAGE

| | |
|-----------------------------------|--|
| Storage Temperature: | Store between 40–100F (4–38C). |
| Handling and Storage Precautions: | Keep away from heat, sparks and flame. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Vapors may cause flash fire or ignite explosively. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. Avoid contact with eyes and clothing. Avoid prolonged or repeated contact with skin. Close container after each use. Wash thoroughly after handling. |

10. TOXICOLOGICAL DATA

| | |
|----------|---|
| General: | NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. No additional information provided for this product. See Section 2 for chemical specific data. |
|----------|---|

11. ECOLOGICAL DATA

| | |
|----------|--|
| General: | No additional information provided for this product. See Section 2 for chemical specific data. |
|----------|--|

12. ACCIDENTAL RELEASE MEASURES

| | |
|----------------------------|---|
| Spill Response Procedures: | ELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area). Use only non-sparking equipment to handle spilled material and absorbent. Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to containers. Use non-sparking tools to collect absorbed material. |
| Public Safety: | CALL CHEMTREC at (800)–424–9300 for emergency response. Isolate spill or leak area immediately for at least 50 meters (150 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. |

OD3300_E2

Ventilate closed spaces before entering. LARGE SPILLS: Consider initial downwind evacuation for at least 300 meters (1000 feet).
Also, Reference Emergency Response Guide Number: 128

13. DISPOSAL CONSIDERATION

| | |
|-----------------|--|
| Waste Disposal: | Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Section 15 if listed). |
|-----------------|--|

14. TRANSPORTATION INFORMATION

| DOT (Domestic Surface Transportation) | | IMO / IMDG (Ocean Transportation) | |
|---------------------------------------|----------------------------|-----------------------------------|--------------------------------------|
| DOT Proper Shipping Name: | PAINT | IMDG Proper Shipping Name: | PAINT |
| DOT Hazard Class: | 3 | IMDG Hazard Class: | 3 – Flammable and Combustible liquid |
| UN / NA Number: | UN 1263 | UN Number: | UN 1263 |
| DOT Packing Group: | III | IMDG Packing Group: | III |
| CERCLA/DOT RQ: | 296006 gal. / 2267574 lbs. | System Reference Code: | 1 |

15. REGULATORY INFORMATION

| | |
|---|--|
| Regulatory Overview: | The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be listed on the TSCA Inventory. Note: Any chemical ingredients listed in Section 15, that do not also appear in Section 2, are contained in the product at a concentration below the applicable OSHA threshold level of 1% or 0.1%. |
| WHMIS Classification: | No Established Limit |
| Regulatory List | Product Ingredients on List |
| DOT Marine Pollutants (10%): (No Product Ingredients Listed) | |
| DOT Severe Marine Pollutants (1%): (No Product Ingredients Listed) | |
| EPCRA 311/312 Chemicals and RQs (>.1%) : | |
| 0007664–38–2 | Phosphoric acid : 5000 lb final RQ; 2270 kg final RQ |
| EPCRA 302 Extremely Hazardous (>.1%) : | |
| (No Product Ingredients Listed) | |
| EPCRA 313 Toxic Chemicals (>.1%) : | |
| (No Product Ingredients Listed) | |
| Mass RTK Substances (>1%) : | |
| 0000107–98–2 | Propylene glycol monomethyl ether |
| Mass Extraordinarily Haz Sub (>.01%) : | |
| (No Product Ingredients Listed) | |
| Penn RTK Substances (>1%) : | |
| 0000107–98–2 | Propylene glycol monomethyl ether |
| Penn Special Hazardous Substances (>.01%) : | |
| (No Product Ingredients Listed) | |
| Rhode Island Hazardous | |

Substances (>.1%) :

| | |
|--------------|-----------------------------------|
| 0007664-38-2 | Phosphoric acid |
| 0000107-98-2 | Propylene glycol monomethyl ether |

RCRA Status:
(No Product Ingredients Listed)

N.J. RTK Substances (>1%) :

| | |
|--------------|-----------------------------------|
| 0000107-98-2 | Propylene glycol monomethyl ether |
|--------------|-----------------------------------|

N.J. Special Hazardous Substances (>.01%) :

| | |
|--------------|-----------------------------------|
| 0007664-38-2 | Phosphoric acid |
| 0000107-98-2 | Propylene glycol monomethyl ether |

N.J. Env. Hazardous Substances (>.1%) :

(No Product Ingredients Listed)

Proposition 65 – Carcinogens (>0%):
(No Product Ingredients Listed)

Proposition 65 – Female Repro Toxins (>0%):
(No Product Ingredients Listed)

Proposition 65 – Male Repro Toxins (>0%):
(No Product Ingredients Listed)

Proposition 65 – Developmental Toxins (>0%):
(No Product Ingredients Listed)

16. OTHER INFORMATION

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

FOR PROFESSIONAL USE ONLY

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.

Head Office

International Paint, LLC, 6001 Antoine Drive, Houston, Texas 77091. <http://www.international-pc.com> or <http://www.international-marine.com>

End Of Document