






11 33oz

51 169oz









Wood & teak waterproofing

Properties

WOOD & TEAK WATERPROOFING is a treatment product that makes all types of wooden surfaces hydrophobic, thereby waterproofing them and protecting them long term against damage caused by water, humidity, weather, waterborne dirt (mould, stains, rings), and wood swelling or shrinkage.

ADVANTAGES:

- ·Water-based product.
- ·Non-flammable.
- •PFAS-free (fluoropolymer family considered 'forever chemicals' as they degrade very little in the environment and may build up in air, water, soil, and living organisms).
- ·Excellent hydrophobic properties.
- ·Long-lasting water-repellent effect.
- ·Significantly reduces the capillary absorption of wood, particularly after ageing and exposure to the elements.
- ·Easy to apply.
- ·Quick drying.

Instructions for use

Respect usual safety measures for the use of chemical products and wear the appropriate individual protection equipment.

WOOD & TEAK WATERPROOFING is used undiluted on a clean, dry surface. For precleaning, we recommend using either our T17 TEAK STEP 1 and T18 TEAK STEP 2 products, or our T20 WOOD & TEAK CLEANING POWDER.

Mix well before use. Apply generously and evenly with a brush or roller onto the surface to be treated, ensuring it becomes damp.

Leave it to dry for a few hours at room temperature. The wood is then protected.

Technical specifications

Physical state: liquid Colour: white pH: ca. 7,5 Density: ca. 1

Storage: keep tightly closed and protected from cold, frost, UV rays and heat in a ventilated

References and packaging

NCT22ML-1 Bottle 11 / 33oz NCT22ML-5 Can 5l / 169oz

We disclaim any responsibility for handling, storage, use or disposal of the product which will differ from the recommendations of FLOWEY®.







